



Multi-position, telescopic parking stands provide a convenient means of storing ANVER lifters when not in use. They permit storage of the lifter with the vacuum pad seals off the ground, reducing the chance of damage to the seals.

Available in three different styles depending on lift frame:

- Bolt-on to end of beam
- Adjustable on beams with welded angle (mounted below main beam)
- Adjustable on a slide along the main beam for longer lifters

| Part Number | Item Number | Leg Length in. (mm) | For Use With | Mounting | Pair Weight lb (kg) |
|-------------|-------------|---------------------|-------------------|--------------------------|---------------------|
| 72000222 | 72000222 | 22 (559) | End of 3x6 Beams | M10 | 115 (52) |
| 72000189 | 72000189 | 22 (559) | End of 5x7 Beams | M12 | 128 (58) |
| 72000164 | 72000164 | 27.5 (699) | 5x7 Beams | Adjustable Slide Mounted | 161 (73) |
| 72000158 | 72000158 | 27.5 (699) | 6x8 Beams | Adjustable Slide Mounted | 165 (75) |
| PST20-19-21 | 72000205 | 21 (533) | GFT Series Frames | Adjustable Beneath Beam | 115 (52) |
| PST30-31-21 | 72000209 | 21 (533) | GFT Series Frames | Adjustable Beneath Beam | 116 (53) |
| PST45-31-21 | 72000206 | 21 (533) | GFT Series Frames | Adjustable Beneath Beam | 129 (59) |
| PST67-31-24 | 72000206 | 24 (610) | GFT Series Frames | Adjustable Beneath Beam | 135 (61) |



Spring loaded red knob will snap into position and lock the parking stands as you adjust them. The pin diameter is a robust one inch (25.4 mm) for security even on heavy lifters. Slanted "A" Frame construction ensures stability.