










**Fittings which Push-In from the Bottom for ANVER Group 2 Universal Suction Cups**

- ANVER divides small universal suction cups into three groups based on mounting specifications and style. Group Two Fittings, shown here, are those that push in from the bottom, exposing a male thread at the top of the cup.
- Within each vacuum fitting group, the hardware is interchangeable with all other cups within the group. Any Group 2 fitting will fit any Group 2 cup.
- These all-metal, electro-less nickel-plated brass fittings are reusable. Once you buy the cups with fittings, you only need to buy replacement rubber cups in the future.
- The cup is held from the bottom flange of the fitting, which is screwed into a female connection above the cup to hold it tight. Replacement takes only a few seconds – simply unscrew the fitting, replace the cup, and screw the fitting back on using your hand or screw driver. Made by ANVER Corp. in the USA.

Product Photo	Part No.	Connection	Thru Hole Dia. or Thread [in. (mm)]	H Height [in. (mm)]	Weight [grams]
	HS5	M5 (5 mm) male	0.11 (2.7)	0.71 (18)	7.6
	HS10-32	10-32 UNF male	0.1 (2.5)	0.71 (18)	7.6
	HS6	M6 (6 mm) male	0.14 (3.5)	0.79 (20)	7.4
	HS8	M8 (8 mm) male	0.2 (5.1)	0.79 (20)	6.6



Product Photo	Part No.	Connection		Thru Hole [in. (mm)]	Hex Size [in. (mm)]	L Added Height [in. (mm)]	H Overall Height [in. (mm)]	Weight [grams]
	B18F-G	G1/8" female		0.13 (3.6)	0.55 (14.0)	0.47 (12.0)	-	4.1
	B18F	1/8" NPT female		0.17 (4.2)	0.5 (12.6)	0.47 (12.0)	-	8.1
	B18M	1/8" NPT male	10-32 UNF female	0.17 (4.2)	0.5 (12.6)	0.21 (5.2)	0.51 (13.0)	9.9
	B18M-G	G1/8" male	M5 (5 mm) female	0.14 (3.5)	0.55 (14.0)	0.24 (6.0)	0.53 (13.5)	12