

## High Flow Reinforced Plastic Vacuum Hose

Doc. No. 13600244A



## **Features**

High strength fiber reinforced PVC hose cover bonded to coated spring steel helix. The FT Series Vacuum Hose offers excellent flexibility for use with vacuum pad attachments that require bending in tight areas.

## Applications:

Excellent for all commercial or industrial vacuum handling applications where medium to high vacuum flow is required. The flexibility of the hose makes it suitable for "high bend" applications without wall collapse under vacuum. Due to its flexibility, this hose shrinks along its length under vacuum; therefore, hose clamps are required.

## Specifications:

• Vacuum: 29" Hg

• Temperature: -20° to 150°F (-29° to 66°C)

· Color: Grey

**Note:** Available by the inch up to 600" (50 ft) spools. For RFQs, please specify inches when entering quantity.

Item Number	Inside Diameter in. (mm)	Features
FTSVF075	0.75 (19.0)	Wire Reinforced, Grey
FTSVF100	1 (25.4)	Wire Reinforced, Grey
FTSVF125	1¼ (31.2)	Wire Reinforced, Grey
FTSVF150	1½ (38.1)	Wire Reinforced, Grey
FTSVF200	2 (50.1)	Wire Reinforced, Grey
FTSVF250	2½ (63.5)	Wire Reinforced, Grey
FTSVF300	3 (76.2)	Wire Reinforced, Grey