



Construction:

- All fitting threads meet standards from DrySeal American Standard Taper Pipe Thread (NPTF)
- Made from CA 360 and CA 345 brass
- Top quality finish
- Meet functional requirements of SAE J512, American Society of Mechanical Engineers (ASME), and American Standards Association (ASA)
- National Pipe Taper (NPT) or metric sizes available
- Precision machined

Applications:

ANVER fittings have been designed for vacuum or medium pressure line connections, and they are used in conjunction with ANVER wire reinforced vacuum hose and worm gear drive hose clamps.

Specifications:

- Max. pressure: 1000 psi
- Vacuum: 30 in. Hg
- Temperature: -65° to 250°F (-54° to +121°C)

NPT Tapered Thread Hose Barbs

Item Number	Description
A1814B	Hose Barb, 1/8" NPT x 1/4" (6.4 mm) Hose
A1838B	Hose Barb, 1/8" NPT x 3/8" (9.5 mm) Hose
A1412B	Hose Barb, 1/4" NPT x 1/2" (12.7 mm) Hose
A1414B	Hose Barb, 1/4" NPT x 1/4" (6.4 mm) Hose
A1438B	Hose Barb, 1/4" NPT x 3/8" (9.5 mm) Hose
A3812B	Hose Barb, 3/8" NPT x 1/2" (12.7 mm) Hose
A3814B	Hose Barb, 3/8" NPT x 1/4" (6.4 mm) Hose
A3838B	Hose Barb, 3/8" NPT x 3/8" (9.5 mm) Hose

G (BSPP*) Straight Thread Hose Barbs

Item Number	Description
A14G14B	Hose Barb, 1/4" BSPP x 1/4" (6.4 mm) Hose
A38G38B	Hose Barb, 3/8" BSPP x 3/8" (9.5 mm) Hose
A12G12B	Hose Barb, 1/2" BSPP x 1/2" (12.7 mm) Hose